

UV performance: 400

European Standard (EN 1836:2005)

Filter Category	3
Filter Type	Polarizing
Transmittance requirements	
Luminous Tran. (380-780nm)	11.88%
Maximum Spectral Tran. (280-315nm)	0.00% Pass
Maximum Spectral Tran. (315-350nm)	0.00% Pass
Maximum Solar UVA Tran. (315-380nm)	0.00% Pass
100% protection claim (optional)	
Solar UVB Tran. (280-315nm)	0.00% Pass
Solar UVA Tran. (315-380nm)	0.00% Pass
Solar UV Tran. (280-380nm)	0.00% Pass
Solar Blue Light Tran. (380-500nm)	12.12%
Solar Infrared Tran. (780-2000nm)	N/A
Road use and driving requirements	
Minimum Spectral Tran. (500-650nm)	10.43% Pass
● Red Q Quotient	1.09 Pass
● Yellow Q Quotient	0.98 Pass
● Green Q Quotient	1.02 Pass
● Blue Q Quotient	1.19 Pass

American Standard (ANSI Z80.3:2008)

Lens Type	Type I Polarizing	
Primary Function and Shade	General purpose lens	
UVB Exposure Category	High and prolonged exposure	
UVA Exposure Category	High and prolonged exposure	
Transmittance requirements		
Luminous Tran. (380-780nm)	11.87% Pass	
Mean Tran. UVB or Erythema Zone (290-315nm)	0.00% Pass	
Mean Tran. UVA or Near Zone (315-380nm)	0.00% Pass	
Near Infrared Tran. (780-1400nm)	N/A	
Road use and driving requirements		
Spectral Transmittance		
Minimum Spectral Tran. (500-650nm)	10.43% Pass	
Colour limits		
Yellow Traffic Signal, X Chromaticity Coordinate	0.592	Pass: see chart
Yellow Traffic Signal, Y Chromaticity Coordinate	0.407	
Green Traffic Signal, X Chromaticity Coordinate	0.192	
Green Traffic Signal, Y Chromaticity Coordinate	0.385	
Average Daylight, D65 X Chromaticity Coordinate	0.304	
Average Daylight, D65 Y Chromaticity Coordinate	0.319	
Traffic Signal Transmittance		
● Red Traffic Signal Transmittance	1510% Pass	
● Yellow Traffic Signal Transmittance	11.55% Pass	
● Green Traffic Signal Transmittance	12.09% Pass	

Australian Standard (AS/NZS 1067:2003)

Filter Category	3
Filter Type	Polarizing
Transmittance requirements	
Luminous Tran. (380-780nm)	11.88%
Maximum Spectral Tran. (280-315nm)	0.00% Pass
Maximum Spectral Tran. (315-350nm)	0.00% Pass
Maximum Solar UVA Tran. (315-400nm)	0.00% Pass
Minimum Spectral Tran. (450-650nm)	10.43% Pass
100% protection claim (optional)	
Solar UVB Tran. (280-315nm)	0.00% Pass
Solar UVA Tran. (315-400nm)	0.00% Pass
Solar UV Tran. (280-400nm)	0.00% Pass
Solar Blue Light Tran. (400-500nm)	12.15%
Solar Infrared Tran. (780-2000nm)	N/A
Road use and driving requirements	
● Red Q Quotient	1.09 Pass
● Yellow Q Quotient	0.98 Pass
● Green Q Quotient	1.02 Pass
● Blue Q Quotient	1.19 Pass

